HALLTECH Inc.
465 Coronation Drive
Toronto, ON M1E 2K2
Phone: 416-284 6111
Fax: 416-284 6932

POLYCOL, Une division de Halltech Inc.
2805 Rue Botham
Ville St-Laurent, QC H4S 1H8
Phone: 514-331 2710
Fax: 514-331 8987

SUPERGRIP 1134 *Technical Data Sheet*

Supergrip 1134 is a vinyl acetate copolymer emulsion adhesive.

PHYSICAL CHARACTERISTICS

Total solids %:	61.0 – 66.0
Viscosity @ 24°C, cps:	1200 – 2000 RVF, Spindle #3, 20 rpm
Relative Density:	1.07 – 1.09
pH value:	4.5 – 6.5
VOC:	<0.4%
Colour of Dried Film:	Light, translucent
Cleaner:	Water (wet), MEK (dry)
Application Method:	Roller wheel
Shelf Life:	6 months

APPLICATIONS AND FEATURES

Supergrip 1134 is a general-purpose laminating adhesive with excellent lay-flat properties.

There is (NO WARRANTY OR CONDITION OF ANY KIND) written or oral, expressed or implied (INCLUDING NO WARRANTY OR MERCHANTABILITY OR FITNESS OF THE GOODS FOR THE PURPOSE OF CONTEMPLATED BY BUYER) concerning the goods sold and hereunder or containers in which shipped and none shall be implied by law, EXCEPT THAT THE GOODS SHALL BE IN ACCORDANCE WITH SELLER'S SPECIFICATIONS.