HALLTECH Inc.
465 Coronation Drive
Toronto, ON M1E 2K2
Phone: 416-284 6111
Fax: 416-284 6932

POLYCOL, Une division de Halltech Inc.
2805 Rue Botham
Ville St-Laurent, QC H4S 1H8
Phone: 514-331 2710
Fax: 514-331 8987

SUPERSET 133 V4 *Technical Data Sheet*

Superset 133 V4 is a polyvinyl acetate emulsion adhesive.

PHYSICAL CHARACTERISTICS

Total solids %:	45.0 – 49.0
Viscosity @ 24°C, cps:	350 – 450
	RVF, Spindle #2, 20 rpm
Relative Density:	1.09 – 1.11
pH value:	4.5 – 5.5
Colour of Dried Film:	Light, translucent
Cleaner:	Water (wet), MEK (dry)
Application Method:	Brush or roller
Shelf Life:	3 months
VOC:	9.97 g/L

APPLICATIONS AND FEATURES

Superset 133 V4 is a synthetic resin emulsion used to harden the edges of fibreglass boards.

There is (NO WARRANTY OR CONDITION OF ANY KIND) written or oral, expressed or implied (INCLUDING NO WARRANTY OR MERCHANTABILITY OR FITNESS OF THE GOODS FOR THE PURPOSE OF CONTEMPLATED BY BUYER) concerning the goods sold and hereunder or containers in which shipped and none shall be implied by law, EXCEPT THAT THE GOODS SHALL BE IN ACCORDANCE WITH SELLER'S SPECIFICATIONS.