HALLTECH Inc.
465 Coronation Drive
Toronto, ON M1E 2K2
Phone: 416-284 6111
Fax: 416-284 6932

POLYCOL, Une division de Halltech Inc.
2805 Rue Botham
Ville St-Laurent, QC H4S 1H8
Phone: 514-331 2710
Fax: 514-331 8987

TS 482 V3 *Technical Data Sheet*

TS 482 V3 is a vinyl acetate-ethylene copolymer emulsion adhesive.

PHYSICAL CHARACTERISTICS

Total solids %:	49.5 – 51.5
Viscosity @ 24°C, cps:	250 – 300 RVF, Spindle #2, 20 rpm
Relative Density:	1.06 – 1.08
pH value:	4.0 – 5.0
VOC:	2.5 g/L
Colour of Dried Film:	Translucent
Cleaner:	Water (wet), MEK (dry)
Application Method:	Extruder or electronic applicator
Shelf Life:	9 months

APPLICATIONS AND FEATURES

TS 482 V3 is a fast-setting, clean-running, vinyl acetate-ethylene copolymer emulsion adhesive for bonding difficult surfaces (e.g., dense clay coatings, plastic coatings, etc.) using an extruder or electronic glue applicator.

There is (NO WARRANTY OR CONDITION OF ANY KIND) written or oral, expressed or implied (INCLUDING NO WARRANTY OR MERCHANTABILITY OR FITNESS OF THE GOODS FOR THE PURPOSE OF CONTEMPLATED BY BUYER) concerning the goods sold and hereunder or containers in which shipped and none shall be implied by law, EXCEPT THAT THE GOODS SHALL BE IN ACCORDANCE WITH SELLER'S SPECIFICATIONS.